

IFP-FFT

Fire Fighters Telephone Control System

The IFP-FFT is a Fire Fighters Telephone communication system. The IFP-FFT Fire Fighter Telephone System provides supervision, annunciation, and control for local and remote telephone handsets. The IFP-FFT with keypad, provides indications of phone activation, and corresponding trouble conditions. The FFT-24 expander board lets you add additional zones to the IFP-FFT.

The IFP-FFT can use up to two FFT-24s for a total of 72 zones. Each zone consists of one addressable monitor module (IDP-Minimon) and a minimum of one Fire Fighter Telephone Jack (FFT-FPJ).

INSTALLATION

The IFP-FFT can be surface or flush mounted. Use VIP-TR Trim Ring for flush mounting.

COMPATIBILITY

The IFP-FFT is compatible with the following FACPs:

- IFP-2100ECS / IFP-2100ECSB (120V or 240V)
- IFP-2100 / IFP-2100B / RFP-2100 / RFP-2100B (120V or 240V)
- IFP-2000 / RPS-2000 / IFP-2000ECS (120V or 240V)
- IFP-300 / IFP-300B / IFP-300ECS / IFP-300ECSB
- IFP-1000 / IFP-1000ECS (120V or 240V)
- IFP-100 / IFP-100ECS
- IFP-75
- IFP-50
- RPS-1000

FEATURES & BENEFITS

- IFP-FFT Fire Fighter Telephone module for control and annunciation of up to 72 remote telephone jacks
- A maximum of 10 Fire Fighter Remote Handsets (FFT-RHS) can be used at one time to communicate over the telephone circuit connected to the IFP-FFT
- Fire Fighter Phone Jack (FFT-FPJ) provides a plug-in location for the FFT-RHS
- Single telephone station mount comes in a lockable cabinet containing one remote handset. Available in Recessed mount (FFT-STSR) or surface mount (FFT-STSS).
- Fire Fighter Handset Cabinet (FFT-HSC) is used to store ten fire fighter handsets (FFT-RHS)
- System Status LEDs
- Supports two FFT-24 zone expanders
- The IFP-FFT supports up to 72 IDP-Minimon devices on one FFT system
- Simplified installation by using single loop design
- JumpStart® auto-programming
- For retrofit projects, IFP-FFT is compatible with any UL listed 24V regulated power supply



IFP-FFT

IFP-FFT Technical Specifications

PHYSICAL

Flush Mount Dimensions: 20¼" W x 26¾" H x 2.5" – 3" D (51.4 W x 68 H x 6.4–7.6 D cm)

Overall Dimensions: 20" W x 26½" H x 4.6" D (50.75 W x 67.3 H x 11.8 D cm)

Weight: 53 lbs.

Color: Red

ENVIRONMENTAL

Operating Temperature: 32°F to 120°F (0°C to 49°C)

Humidity: 10 to 93% relative humidity (non-condensing)

ELECTRICAL:

Voltage for the IFP-FFT must be a power-limited, filtered, non resettable nominal 24 VDC source.

The voltage source must be within the range of 17-29 VDC.

Active Current: 230 mA

Standby Current: 120 mA

SLC Circuit: 32V; 150mA

Audio Circuits: 17V; 53mA

AGENCY LISTINGS AND APPROVALS

UL Listed

ORDERING INFORMATION

IFP-FFT: Fire Fighters Telephone

IDP-Minimon: Mini monitor module

IDP-ISO: Fault Isolator Module

ECS ACCESSORIES

FFT-24: 24 Zone Expander

FFT-FPJ: Remote Phone Jack

FFT-RHS: Fire Fighters Remote Hand Set

FFT-HSC: Fire Fighters Handset Cabinet. Holds up to 10 remote handsets

FFT-STSR: Single Telephone Station Recessed. A lockable cabinet containing one remote handset.

FFT-STSS: Single Telephone Station Surface Mount. A lockable cabinet containing one remote handset.

FFT-BGK: Break Glass Kit for FFT-STS

VIP-TR: Flush Mount Trim Ring

For a complete listing of all compliance approvals and certifications, please visit www.farenhyt.com.

Microsoft, Windows, and the Windows Logo are registered trademarks or trademarks of Microsoft Corporation.

Honeywell® is a registered trademarks of and Farenhyt™ is a trademark of Honeywell International, Inc.

This document is not intended to be used for installation purposes. We try to keep our product information up-to date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

For Technical Support, call 800-446-6444.

For more information

Learn more about Honeywell's Farenhyt Series and other products available by visiting www.farenhyt.com

Honeywell Farenhyt

12 Clintonville Road
Northford, CT 06472
800-328-0103

Doc 351549 | E | 02/18
© 2018 Honeywell International Inc.

Honeywell