

IDP-Control

Addressable Notification Module

General

The IDP-CONTROL is an addressable notification module for use with Honeywell Farenhyt Series fire alarm control panels (FACPs). The IDP-CONTROL gives you the flexibility to add notification circuits wherever they are needed on an Farenhyt FACP signaling line circuit (SLC) loop.

The IDP-CONTROL provides supervised monitoring of wiring to load devices that require an external power supply to operate, such as bells, horns, and strobes. It is capable of Class B and Class A supervision.

Upon command from the FACP, the IDP-CONTROL will disconnect the supervision and connect the external power supply across the load device. The disconnection of the supervision provides a positive indication to the panel that the control relay actually turned on. The external power supply is always relay isolated from the SLC loop, so that a trouble condition on the power supply will never interfere with the rest of the system.

Installation

The IDP-CONTROL mounts directly into a 4" square electrical box. The box must have a minimum depth of 2-1/8". A surface mount electrical box (System Sensor® PN SMB500) is available from Honeywell.

Compatibility

The IDP-CONTROL is compatible with the following Farenhyt Series FACPs: IFP-2100 / IFP-2100ECS / RFP-2100, IFP-2000 / IFP-2000ECS / RPS-2000, IFP-1000 / IFP-1000ECS, IFP-300 / IFP-300ECS, IFP-100 / IFP-100ECS, IFP-75, and IFP-50.



IDP-Control Module

FEATURES & BENEFITS

- Flexible solution for adding notification circuits where needed
- Support for Class B (style Y) or Class A (style Z) wiring
- Panel controlled status LED that flashes green in normal state and is solid red in alarm
- Polling LED visible through the cover plate
- Rotary address switches for fast installation
- SEMS screws for easy wiring
- UL Listed
- CSFM Listed
- MEA Listed 386-02-E Vol. II

IDP-Control Technical Specifications

PHYSICAL

Dimensions: 4.5" H x 4"W x 1.25" D

Shipping Weight: 6.3oz (196g)

ENVIRONMENTAL

Operating Temperature: 32°F to 120°F (0°C to 49°C)

Humidity: 10% to 93% relative humidity (non-condensing)

ELECTRICAL

Operating Voltage: 15 to 32VDC

Standby & Alarm Current: 350 mA

End-of-Line Resistance: 47k

SLC Loop Impedance: 40

ORDERING INFORMATION

IDP-CONTROL: Notification module.

ACCESSORIES

SMB500: 4" Square Surface Mount Electrical Box

CB500: Module Barrier. Used to separate power limited and non-power limited wiring in a junction box

AGENCY LISTINGS

NFPA 13, NFPA 70, NFPA 72, UL 2572, UL 1711 & UL 864: Local Protective Signaling Systems

UL Listed

CSFM:

MEA Listed: 386-02-E, Volume 2.

For a complete listing of all compliance approvals and certifications, please visit: www.Farenhyt.com

Farenhyt™ is a trademark of Honeywell International, Inc.

Honeywell® is a registered trademark of Honeywell International Inc.

This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

For Technical Support, please call 800-446-6444.

Honeywell Fire Solutions

12 Clintonville Road

Northford, CT 06472-1610

203.484.7161